



SAFETY DATA SHEET

FOR AGRICULTURE USE ONLY

Silwet* 408 surfactant

Section 1. Product and company identification

Product name : Silwet* 408 surfactant

Chemical name : Polyalkyleneoxide Modified Heptamethyltrisiloxane

Material uses : Agricultural material

Manufacturer/Importer/Distri

butor Information

Momentive Performance Materials - Sistersville

10851 Energy Highway FRIENDLY WV 26146

Contact person : 4information@momentive.com

Telephone : General information

+1-800-295-2392

Emergency telephone number

Supplier : CHEMTREC

1-800-424-9300

Section 2. Hazards identification

Classification of the substance or

mixture

ACUTE TOXICITY:inhalation - Category 4

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

GHS label elements

Hazard pictograms

(!)

Signal word : Was

Hazard statements : H332 Harmful if inhaled.

H319 Causes serious eye irritation.

Precautionary statements

General : Not for aerosol use

Prevention : Wear eye or face protection.

Use only outdoors or in a well-ventilated area.

Avoid breathing vapor.

Wash hands thoroughly after handling.

Response : IF INHALED:

Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

Call a POISON CENTER or physician if you feel unwell.

IF IN EYES:

Silwet* 408 surfactant Page: 2/12

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention.

Storage : Not applicable.

Disposal : Not applicable.

Other hazards which do not result in classification

None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Chemical name : Polyalkyleneoxide Modified Heptamethyltrisiloxane

Hazardous ingredients	% by weight	CAS
		number
Poly(oxy-1,2-ethanediyl), .alpha[3-[1,3,3,3-tetramethyl-	70 - 100	67674-67-3
1-[(trimethylsilyl)oxy]-1-disiloxanyl]propyl]omega		
hydroxy-		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses.

Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms

occur. Wash clothing before reuse. Clean shoes thoroughly before

reuse.

Ingestion : Wash out mouth with water. Remove victim to fresh air and keep at

rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place

Silwet* 408 surfactant Page: 3/12

in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

Protection of first aid personnel

: No specific treatment.

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media

Use dry chemical, CO2, alcohol-resistant foam or water spray (fog).

water jet

Specific hazards arising from the chemical

Hazardous thermal decomposition products

In a fire or if heated, a pressure increase will occur and the container may burst.

Decomposition products may include the following materials: carbon dioxide

carbon monoxide silicon oxides

Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Special protective equipment for fire-fighters

: Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Silwet* 408 surfactant Page: 4/12

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

Large spill

stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see section 8 of SDS). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker

Silwet* 408 surfactant Page: 5/12

exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid Color : Light yellow

Odor: PolyetherOdor threshold: Not availablepH: Not available

Silwet* 408 surfactant Page:6/12

Melting point -8 °C (17.60 °F) Pour point

Boiling point > 150 °C (302.00 °F) Copolymer.

Flash point 118 °C (244.40 °F) (ASTM D 93)

Burning time Not available Not available **Burning rate**

Evaporation rate < 1

(n-Butyl acetate=1)

Flammability (solid, gas) Not available

Lower: Not available Lower and upper explosive (flammable) limits **Upper:** Not available

Vapor pressure < 1.33 hPa @ 20 °C (68.00 °F)

Vapor density Greater than 1 [Air = 1]

Relative density Not available 1.0200 g/cm3 **Density**

Solubility Not available Solubility in water Dispersible

Partition coefficient: n-3.31 pH 7 octanol/water 3.31 pH 9

Not available **Auto-ignition temperature** Not available **Decomposition temperature** Not available **SADT**

Dvnamic: Not available Viscosity

Kinematic: Not available

Volatile organic content 12.1 g/l

Other information

No additional information.

Section 10. Stability and reactivity

Reactivity Stable under normal conditions.

Chemical stability The product is stable.

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions

will not occur.

Conditions to avoid No specific data.

No specific data. **Incompatible materials**

Hazardous decomposition Under normal conditions of storage and use, hazardous products

decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Silwet* 408 surfactant Page:7/12

Product/ingredient name	Result	Species	Dose	Exposure
Silwet* 408 surfactant				
	LD50 Oral	Rat	> 2,000 mg/kg	-
	LC50	Rat	> 11.78 mg/l	4 h
	Inhalation			
	(Aerosols)			
	(5% Diluted			
	aqueous			
	solution. The			
	health hazard			
	evaluation is			
	based on the			
	toxicological			
	properties of a			
	similar			
	material.)			
	LC50	Rat	2 mg/l	4 h
	Inhalation			
	(Aerosols)			
	(The health			
	hazard			
	evaluation is			
	based on the			
	toxicological			
	properties of a			
	similar			
	material.)			
	LD50 Dermal	Rat	> 2,000 mg/kg	-
Conclusion/Summary	: Not	determined		

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Silwet* 408 surfactant	eyes OECD- Guideline 405 (Acute Eye Irritation/C orrosion)	Rabbit			-
Remarks:	Causes eye irritation.				
	Skin	Rabbit			-
Remarks:	Non-irritant to skin.		<u>.</u>		

Conclusion/Summary

Not determined Skin Not determined eyes Respiratory Not determined

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Silwet* 408 surfactant	-	Guinea pig	Did not cause
			sensitization on
			laboratory animals.

Conclusion/Summary

Not determined Skin Respiratory Not determined

Silwet* 408 surfactant Page:8/12

Mutagenicity

Conclusion/Summary Not determined

Carcinogenicity

Not determined **Conclusion/Summary**

Reproductive toxicity

Not determined **Conclusion/Summary**

Teratogenicity

Not determined **Conclusion/Summary**

Specific target organ toxicity (single exposure)

Not available

Specific target organ toxicity (repeated exposure)

Not available

Aspiration hazard

Not available

Information on the likely routes of : Not available

exposure

Potential acute health effects

Eye contact Causes serious eye irritation.

Inhalation Harmful if inhaled.

Skin contact No known significant effects or critical hazards.

Ingestion Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Adverse symptoms may include the following: Eye contact

> pain or irritation watering

redness

Inhalation No specific data. **Skin contact** No specific data. Ingestion No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Not available **Potential immediate effects** Potential delayed effects Not available

Long term exposure

Potential immediate effects Not available Not available **Potential delayed effects**

Potential chronic health effects

Silwet* 408 surfactant Page: 9/12

Conclusion/Summary : Not determined

General: No known significant effects or critical hazards.Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: This material was not mutagenic in an Ames bacterial assay.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available

Other information

This material was not mutagenic in an Ames bacterial assay or in three mammalian test systems including the Chinese hamster ovary (CHO)/HGPRT gene mutation assay, a micronucleus cytogenetic assay in mice, and an in vitro mammalian cytogenetic test.

In a repeated skin application study with rats, this material caused moderate skin irritation which resolved during a post-application recovery period. There was no evidence for percutaneous cumulative or specific organ toxicity, and no effect on male or female reproductive systems.

Findings from a 14-day dietary feeding study with rats show that high dosage repeated ingestion of this material causes reversible adverse effects on the male and female reproductive tracts. Additional effects seen include increased liver weight, altered blood cytology/chemistry, and thyroid enlargement (primarily hypertrophy, with some hyperplasia). Evidence of partial or complete recovery was found over a 28-day recovery period.

Findings from a repeat 9-day aerosol inhalation toxicity study with rats show a no-observable-effect-level (NOEL) of less than 0.025 mg/l. Symptoms of toxicity included rales, gasping, ocular opacity, prostration, hypothermia, reduced body weight gain and food consumption, changes in clinical pathology, decreased thymus weight, and microscopic lesions in the nasal cavity. There was no effect on the male or female reproductive systems. It is not anticipated that the use of aqueous dilutions of this product would result in this type of aerosol exposure.

Section 12. Ecological information

Ecotoxicity

Product/ingredient name	Result	Species	Exposure
Silwet* 408 surfactant			
	Acute LC50 6.8 mg/l	Fish - Zebrafish	96 h
	Acute EC50 32 mg/l	Aquatic plants -	96 h
	_	Pseudokirchneriella	
		subcapitata	

Conclusion/Summary : Not available

Persistence/degradability

Product/ingredient Test	Result	Dose	Inoculum
-------------------------	--------	------	----------

Silwet* 408 surfactant Page: 10/12

name				
Polyalkyleneoxide		-		
Modified				
Heptamethyltrisiloxane				
Remarks:	The product is not readily biodegradable.			

Conclusion/Summary : Not available

Bioaccumulative potential

Product/ingredient name	Species	Exposure	LogPow	BCF	Potential
Silwet* 408 surfactant			3.313.31	-	low

Mobility in soil

Soil/water partition coefficient

(KOC)

Other adverse effects

: Not available

 Aqueous abiotic hydrolysis expected to contribute to degradation -OECD 111No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. See Section 8 for information on appropriate personal protective equipment.

Section 14. Transport information

DOT SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.(Polyalkyleneoxide Modified Heptamethyltrisiloxane)

DOT HAZARD CLASS:9DOT LABEL (S):9UN/NA NUMBER:UN3082PACKING GROUP:III

IMDG SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.(Polyalkyleneoxide Modified Heptamethyltrisiloxane)

CLASS: 9
IMDG-Labels: 9
UN NUMBER: UN3082
PACKING GROUP: III
EmS No.: F-A; S-F

Silwet* 408 surfactant Page:11/12

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.(Polyalkyleneoxide Modified Heptamethyltrisiloxane)

CLASS: ICAO-Labels: 9MI UN3082 **UN NUMBER: PACKING GROUP:** Ш

Special precautions for user

This substance/preparation meets the criteria of a Marine Pollutant (see IMDG paragraph 2.9.3.3) but is not identified in the IMDG Code (Marpol list). As such, substance/preparation shall be transported as a marine pollutant in accordance with the IMDG code.

15.Regulatory information

United States

United States - TSCA 12(b) - Chemical export notification: None U.S. Federal regulations

required.

United States - TSCA 5(a)2 - Final significant new use rules: Not

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed

SARA 311/312

Classification Immediate (acute) health hazard

California Prop. 65: None required.

Canada

Not reviewed. WHMIS (Canada)

International regulations

International lists Australia inventory (AICS): All components are listed or exempted.

> **Canada inventory:** All components are listed or exempted. **Japan inventory:** All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted. United States inventory (TSCA 8b): All components are listed or exempted. New Zealand Inventory (NZIoC): All components are listed or exempted. Taiwan inventory (CSNN): All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System III (U.S.A.):

Health	2
Flammability	1

Silwet* 408 surfactant Page: 12/12

Physical hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

Full text of abbreviated H

statements

Not applicable.

History

Date of printing: 01/27/2016Date of issue/Date of revision: 05/11/2015Date of previous issue: 00/00/0000Version: 1.0

Prepared by: Product Safety StewardshipKey to abbreviations: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations Not available

Notice to reader

References

Unless otherwise specified in section 1, Momentive Products are intended for industrial application only. They are not intended for specific medical applications, neither for long-lasting (> 30 days) implantation into the human body, injected or directly ingested, nor for the manufacture of multiple usable contraceptives Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

®,*, and TM indicate trademarks owned by or licensed to Momentive.